

### ASG flat slings, 1-ply



- Cost-effective endless flat sling for single use
- Label in standard-compliant signal colour

### ASG endless flat slings – perfect for single use

With the standard-compliant ASG endless flat slings SpanSet offers you particularly cost-effective lifting gear for single use. This means: The endless flat sling is used e. g. for transporting articles from the manufacturer to the construction site. As soon as the cargo arrives at its final destination, the endless flat slings are severed and disposed of. The single-use endless flat slings are thus ideal for use in timber frame and prefabricated building.

The orange-coloured label of the endless flat slings provides details of the load capacity, manufacturer, length, manufacturing date, lifting factors and much more. The ASG endless flat slings can be used across all industries.

Nominal carrying capacity [kg]	Load capacity single layer [kg]	Order number	L1 min. [m]	Approx. strap width [mm]	Approx. strap thickness [mm]	Approx. weight per m circumference [kg]
<b>750</b>	<b>1.500</b>	<b>D036387</b>	0,300	50	1,3	0,041
<b>750</b>	<b>1.500</b>	<b>D049805</b>	0,325	50	1,3	0,050
<b>750</b>	<b>1.500</b>	<b>D037626</b>	0,400	50	1,3	0,060
<b>750</b>	<b>1.500</b>	<b>D035716</b>	0,425	50	1,3	0,063
<b>1.500</b>	<b>3.000</b>	<b>D039580</b>	0,300	50	2,8	0,080
<b>1.500</b>	<b>3.000</b>	<b>D037816</b>	0,400	50	2,8	0,091
<b>1.500</b>	<b>3.000</b>	<b>D039586</b>	0,500	50	2,8	0,109
<b>1.500</b>	<b>3.000</b>	<b>D036137</b>	0,600	50	2,8	0,128

**i** Single-use flat slings manufactured in accordance with DIN 60005. Special designs available on request.

