


02.3 ROUND SLINGS AND MULTI-LEG SLINGS

Fittings according to DIN EN 1677




– Particularly robust: forged fittings protect the round sling from wear thanks to an intelligent design

Fitting KR



Load capacity [kg]	Order number	B [mm]	D [mm]	L [mm]	Weight [kg]
1.400	D062799	51	13	91	0,29
2.500	D062800	56	16	107	0,53
4.000	D062801	69	18	130	0,79
5.600	D062802	80	20	137	1,10
6.700	D062803	90	22	155	1,50
10.000	D062804	105	26	175	2,30
14.000	D062805	125	32	230	4,40
22.400	D062815	160	40	290	8,60
25.000	D002887	150	38	250	7,00
28.000	D016014	150	40	250	8,00
43.000	D016600	200	50	300	15,00

Fitting LS



Load capacity [kg]	Order number	B [mm]	E [mm]	F [mm]	G [mm]	H [mm]	L [mm]	Weight [kg]
1.500	D000893	24	22	10	17	20	94	0,40
2.500	D016982	26	27	12	17	23	108	0,60
4.000	D016983	35	34	14	23	30	134	1,10
6.700	D001085	42	43	18	28	38	166	2,10
10.000	D016978	51	56	22	36	47	203	4,10
16.000	D001103	61	61	26	42	60	229	6,50
20.000	D006142	73	64	31	43	67	267	8,70
27.000	D015801	81	66	32	51	75	301	13,20
31.500	D009638	93	76	38	61	80	333	18,90

Fitting KR



Fitting LS




Fitting KRR



Fitting KE




Fitting KRR



Load capacity [kg]	Order number	B [mm]	D [mm]	L [mm]	L ₁ [mm]	Weight [kg]
3.000	D062806	56	16	107	165	1,00
5.300	D062807	78	20	138	200	2,20
8.000	D062808	105	26	175	265	3,80
14.000	D062809	125	32	230	345	7,70
21.200	D062810	160	40	290	420	13,00
33.500	D062811	190	50	335	500	24,80
53.000	D016508	260	80	470	750	46,00
70.000	D015827	260	80	470	750	71,00

Fitting KE



Load capacity [kg]	Order number	B [mm]	D [mm]	F [mm]	G [mm]	K [mm]	L [mm]	Weight [kg]
2.000	D001105	40	22	9	26	18	63	0,30
3.150	D001134	57	26	12	30	24	76	0,60
5.300	D001136	53	33	15	37	29	94	1,10
8.000	D001138	67	40	19	44	35	114	1,90
12.500	D001140	80	48	22	53	43	134	3,00
15.000	D004255	125	60	24	70	50	187	7,00
21.200	D008630	150	61	29	86	58	209	11,50
31.500	D001142	155	78	36	100	64	250	20,80