



- Can be positioned during ongoing lifting procedures
- Virtually indestructible
- Permanent dimensional stability

### secutex Clip-SC – protective sleeve with a longitudinal opening

The secutex Clip-SC is quickly attached thanks to the mounting slot on the back. It is preferably used whenever flat slings with or without a protective sleeve are required on a case-by-case basis. Important: The Clip-SC makes for easy handling and short set-up times. The secutex protective layer can be placed softly and flexibly on the load, thereby increasing the radius at the critical edges. The leverage forces are extensively distributed and the load remains undamaged.

#### Optional versatility

secutex Clip-SC is available in versions with different surface finishes and with reinforcement. For more information about secutex and the different surface finishes, see page 14.

#### easyClip

Similar to the Clip-SC in terms of design, but with different material properties, easyClip is the budget-friendly version of the clip sleeve. For more information, ask us about it!

Clip-SC suitable for	Designation Clip-SC	Approx. outside width [mm]	Approx. outside height [mm]	Approx. weight per running m [kg]	PowerStar CS, 4-ply	PowerStar B, 2-ply	Liftfix Flat sling
1.000	SC-30	47	22	0,9		✓	✓
2.000	SC-60	85	23	1,4		✓	✓
	SC-PCS 30	55	30	0,9	✓		
3.000	SC-90	115	25	2,2		✓	✓
4.000	SC-120	145	25	2,9		✓	✓
	SC-PCS 60	90	35	2,1	✓		
5.000	SC-150	175	25	3,4		✓	✓
6.000	SC-180	210	30	4,2		✓	✓
	SC-PCS 90	110	35	2,3	✓		
8.000	SC-240	270	35	5,5		✓	✓
	SC-PCS 120	145	40	3,2	✓		
10.000	SC-300	340	35	6,8		✓	✓

**i** Special designs available on request. Protective sleeves can also be fitted by the user as shown in Fig. 1.



One-sided secutex®-coating, sleeve open at the back for flexible use.




Fig. 1