

02.4 FLAT SLINGS

Liftfix flat sling, 2-ply
0,5 - 10,0 t

- Sectional loop reinforcement
- 2-ply, tear-resistant label



Liftfix HB – flat sling with solid basic equipment

With Liftfix we offer you a flat sling in the usual standard quality with different load capacities ranging from 0.5 t to 10 t. Of course Liftfix is manufactured in accordance with DIN EN 1492-2 and is equipped with a 2-ply label with the writing protected inside. Sectional reinforcement of the flat sling loop protects the sling in the critical area – where it meets the crane hook. Standard-compliant colour coding also prevents confusion of the load capacity.



Nominal carrying capacity [kg]	Loop width [mm]	Loop length [mm]	L1 min. [m]	Strap width [mm]	Strap thickness [mm]	Approx. weight 1st m [kg]	Approx. weight per running m [kg]	Order numbers for standard lengths					
								2 m	3 m	4 m	5 m	6 m	8 m
500	36	150	1,0	36	3,0	0,2	0,1	D002558	D002559	D002560	D002561	D002562	D002563
1.000	30	300	1,0	30	5,2	0,2	0,2	D002564	D002565	D002566	D002567	D002568	D002569
1.500	35	300	1,0	50	6,8	0,4	0,3	D002570	D002571	D002572	D002573	D002574	D002575
2.000	40	300	1,2	60	5,0	0,4	0,3	D002576	D002577	D002578	D002579	D002580	D002581
3.000	50	400	1,5	90	5,0	0,6	0,5	D002630	D002631	D002632	D002633	D002634	D002635
4.000	70	400	1,5	120	6,8	0,9	0,8	D002582	D002583	D002584	D002585	D002586	D002587
5.000	80	500	1,7	150	6,6	1,2	1,0	D002588	D002589	D002590	D002591	D002592	D002593
6.000	100	700	2,1	180	7,2	1,4	1,2	D002594	D002595	D002596	D002597	D002598	D002599
8.000	130	800	2,3	240	7,2	1,8	1,6	D002600	D002601	D002602	D002603	D002604	D002605
10.000	160	1.000	2,6	300	7,4	2,4	2,3	-	D002606	D002607	D002608	D002609	D002610

i Special designs available on request. Also available with D-links on request. Manufactured according to DIN EN 1492-2.



The explanations of the icons can be found on the flap.