



02.4 FLAT SLINGS

secutex SF-1

- One-sided secutex-coating
- Easy to position
- Extremely cut-resistant
- Permanent dimensional stability



secutex SF-1: One contact side and the sleeve side are secutex-coated. Fig. 1



secutex SF-1 – protective sleeve coating on one side

Protective sleeve coating on one side

The secutex SF-1 has been technically designed for optimal use with the SpanSet flat sling range or the SpanSet round slings. The contact side has a secutex coating, is extremely cut-resistant and reduces the formation of creases in the fabric. Easily clipped onto the textile lifting gear, the protective sleeve with the one-sided secutex coating equally protects the lifting gear and the load at „sharp edges“ and rough surfaces.

Designed for the application

secutex SF-1 is available in different surface finishes (page 17), such as „ground“, whose surface is slightly roughened. It is used whenever the contact side comes into contact with small amounts of liquids. The rough surface remains permanently slip-resistant.

If necessary, secutex SF-1 is also available with a two-sided coating in the SF-2 version, which precludes application errors when lifting sharp-edged loads. More on pages 90 et seq.

SF-1 suitable for	Designation SF-1	Approx. outside width [mm]	Approx. outside height [mm]	Approx. weight per running m [kg]	PowerStar CS, 4-ply	PowerStar B, 2-ply	Liftfix Flat sling
1.000	SF-1-30	55	20	0,9		✓	✓
2.000	SF-1-60	85	23	1,4		✓	✓
	SF-1-PCS 30	55	30	0,6	✓		
3.000	SF-1-90	115	25	2,2		✓	✓
4.000	SF-1-120	145	25	2,9		✓	✓
	SF-1-PCS 60	90	35	1,6	✓		
5.000	SF-1-150	175	25	3,4		✓	✓
6.000	SF-1-180	210	30	4,2		✓	✓
	SF-1-PCS 90	110	35	1,7	✓		
8.000	SF-1-240	270	35	5,5		✓	✓
	SF-1-PCS 120	145	40	2,3	✓		
10.000	SF-1-300	340	35	6,8		✓	✓

i Special designs available on request. Protective sleeves can also be fitted by the user as shown in Fig. 1.